

# DUST PALLIATIVE APPLICATIONS

## Hydroc Eco Super XL For Dust Palliative Applications

Because of the amazing wetting ability of HYDROC it is useful in areas where dust is a problem.

Use a concentration of approximately 1 part HYDROC ECO SUPER XL to 80-100 parts water.

### Method of Application:

Spray on. When using in tank trucks fill the water tank with water then add 12 litres (to 10,000 litres water) of HYDROC. Do not reverse the procedure, as foaming will cause filling problems.

### Benefits of HYDROC Eco Super XL

The use of HYDROC should gradually reduce the frequency and amount of water needed to control dust in construction, sand and rock crushing operations, dirt racetracks, and similar areas.

The combined action of colloids and wetting agents suggest the use of HYDROC in areas where dust particles in the air create a potentially explosive environment - i.e. manufacturing operations. Use 1 part HYDROC to 100 parts water and atomise into the air.

HYDROC is economical to use and safe to store.

*HYDROC* the ENVIRONMENTALLY SAFE  
ALTERNATIVE

DA Collett Business Services Pty Ltd  
Trading as  
Hydroc Environmental Products  
ABN: 15 077 763 921

1 Ellesmere Road  
GYMEA BAY, NSW 2227  
PO Box 568  
GYMEA NSW 2227

Phone: 0413 054 814  
Fax: 1800 623 097  
Email: davidcollett@hydroc.com.au

**Working towards a cleaner,  
greener, safe environment**

